

WHAT IS CLAIMED IS:

Sub B1
1. A blood flow measuring apparatus comprising:
irradiation means for irradiating a vessel on an
eye fundus with a laser light;

5 light receiving means for receiving a reflected
light of said laser light; and

calculation means for starting the calculation of
an optimum gain for said light receiving means in
synchronization with the start of irradiation by said
10 irradiation means.

2. A blood flow measuring apparatus according to
claim 1, comprising gain setting means for setting the
gain of said light receiving means based on said
15 optimum gain.

3. A blood flow measuring apparatus according to
claim 2, comprising monitoring means for monitoring the
gain of said light receiving means.

20 4. A blood flow measuring apparatus according to
claim 3, wherein said calculation means is adapted to
terminate, by said monitoring means, the calculation of
the optimum gain in synchronization with the completion
25 of setting of the optimum gain.

5. A blood flow measuring apparatus according to
claim 2, further comprising calculation means for

terminating the calculation of the optimum gain for said light receiving means in synchronization with the termination of irradiation by said irradiation means.

5 6. A blood flow measuring apparatus comprising:
tracking means for tracking a vessel image on an eye fundus;

light receiving means for receiving light from the vessel; and

10 calculation means for starting calculation of an optimum gain for said light receiving means in synchronization with the start of tracking.

15 7. A blood flow measuring apparatus according to claim 6, further comprising gain setting means for setting the gain of said light receiving means based on said optimum gain.

20 8. A blood flow measuring apparatus according to claim 7, further comprising monitoring means for monitoring the gain of said light receiving means.

25 9. A blood flow measuring apparatus according to claim 8, wherein said calculation means is adapted to terminate, by said monitoring means, the calculation of the optimum gain in synchronization with the completion of setting of the optimum gain.

10. A blood flow measuring apparatus according to claim 7, further comprising calculation means for terminating the calculation of the optimum gain for said light receiving means in synchronization with the termination of irradiation by said irradiation means.

11. An ophthalmic apparatus comprising:
illumination means for illuminating an eye fundus area including a specified target region;
detection means for detecting light from said specified region;
tracking means for tracking the movement of the eye fundus, utilizing the detection signal of said detection means;
tracking start input means for providing an input signal for starting the tracking of said tracking means;
gain determination means for determining the amplification gain of said detection means; and
control means for executing in succession a first step of causing, in response to the input signal of said tracking start input means, said gain determination means to determine the gain of said detection means, and a second step of starting the tracking by said tracking means with the gain determined by said first step.

12. An ophthalmic apparatus according to claim

11, wherein said detection means is image taking means for taking the image of said specified region thereby outputting an image signal.

5 13. An ophthalmic apparatus according to claim 11, wherein said tracking is executed by deflecting the illuminating light of said illumination means.

10 14. An ophthalmic apparatus according to claim 11, wherein said specified region is a vessel on the eye fundus.

15 15. An ophthalmic apparatus according to claim 11, wherein the amount of illuminating light of said illumination means is different between before the start of said tracking and during the execution of said tracking, and the gain of said detection means is determined in consideration of the amount of illuminating light during the execution of said
20 tracking.

 16. An ophthalmic apparatus comprising:
 illumination means for illuminating an eye fundus area including a specified target region;
25 image taking means for taking the image of said specified region thereby outputting an image signal;
 process condition determination means for determining a process condition based on a signal in

the vicinity of said specified region, contained in the output signal of said image taking means or in the result obtained by processing said output signal;

5 region extraction means for extracting said specified region according to said process condition determination means; and

auto tracking means for executing automatic tracking of said specified region, based on the output of said region extraction means.

10

17. An ophthalmic apparatus according to claim 16, wherein the signal of said specified region indicates a vessel image, and said process condition determination means is adapted to extract the signal of said vessel image portion only and to execute a
15 normalization process for varying the gain according to the signal of said vessel image portion.

20

18. An ophthalmic apparatus according to claim 17, wherein said process condition determination means includes normalizing range setting means for setting an effective range of the normalization process for varying the gain, according to the signal of said vessel image portion.

25

19. An ophthalmic apparatus according to claim 18, wherein said process condition determination means includes normalizing range varying means for varying an

effective range of the normalization process for varying the gain, according to the signal of said vessel image portion.

5 20. An ophthalmic apparatus according to claim 19, wherein said normalizing range varying means is adapted to vary the effective range of the normalization process according to the diameter of said vessel image.

10 21. An ophthalmic apparatus according to claim 17, wherein, in said normalization process, the gain is varied from a predetermined period after the start of automatic tracking, and is thereafter maintained
15 constant.

22. An ophthalmic inspecting apparatus comprising:

20 illumination means for illuminating an eye fundus area including a specified target region;

 image taking means for taking the image of said specified region thereby outputting an image signal;

 process condition determination means for
determining a process condition based on a signal in
25 the vicinity of said specified region, contained in the output signal of said image taking means or in the result obtained by processing said output signal;

 region extraction means for extracting said

specified region according to said process condition determination means;

display means for displaying the result of processing by said process condition determination

5 means; and

auto tracking means for executing automatic tracking of said specified region, based on the output of said region extraction means.

10
20
30
40
50
60
70
80
90
100
110
120
130
140
150
160
170
180
190
200
210
220
230
240
250
260
270
280
290
300
310
320
330
340
350
360
370
380
390
400
410
420
430
440
450
460
470
480
490
500
510
520
530
540
550
560
570
580
590
600
610
620
630
640
650
660
670
680
690
700
710
720
730
740
750
760
770
780
790
800
810
820
830
840
850
860
870
880
890
900
910
920
930
940
950
960
970
980
990